



Leadership through innovation

Dual Pressure Valve Block-DP Series

High Pressure Valve Block for Low & High Pressure Blowing used in semi & fully automatic "Pet" Blow moulding machines



DP215-1 (EXH NO)
DP215-2 (EXH NC)



DP215-1R
DP215-2R



DP215-1RS
DP215-2RS

Salient Features

- High Flow rate through a 3/4" cylinder port & 1" exhaust port
- Fast Response Time
- Long life with use of Polymer seals
- Compact & Light Weight
- Fully integrated thereby reducing external piping
- Hard anodized body & rigid construction
- Manifold mounted for ease of service
- Inbuilt NRV for Low pressure line
- Inbuilt Regulator for pilot line
- Add on Recovery feature
- Add on high pressure silencer

Specifications

Model No	DP215-1	DP215-2
Exhaust Type	Normally Open	Normally Closed
Port Size	L.P:- 1/2" BSP, H.P:- 3/4", EXH:- 1", CYL:- 3/4"	
Orifice	L.P:- 12mm, H.P:- 16mm, EXH:- 24mm	
Design	Poppet Type, External Pilot Operated	
Operating Pressure	Pilot :- 6 to 8 bar LP:- 2 to 20bar , HP:- 3 to 40bar	
Seals	Polymer	
Body M.O.C	Aluminium	
Coil Voltage	230VAC / 24 VDC	

Mercury Pneumatics Pvt. Ltd.

C-105, Ansa Industrial Estate, Saki Vihar Rd, Andheri (E),
Mumbai - 400072. India. Phone: +91-22-40151020

E-mail: contactus@mercuryindia.net Website: www.mercuryindia.net